



小型トラック用ラジアルタイヤ諸元表

タイヤサイズ	PR 又はLI等	適用リム ()標準リム			対応空気圧 (kPa)	最大負荷能力(kg)	
						単輪	複輪
145R10	6PR	3.00B	3.50B	(4.00B)	350	400	370
145/80R12	80/78N	3.50B	(4.00B)	4.50B	350	450	425
	86/84N	3 1/2 J	4 J	4 1/2 J	450	530	500
145R12	6PR	3.50B	(4.00B)		350	450	425
	8PR	3 1/2 J	4 J		450	520	495
155R12	6PR	4.00B	(4.50B)		350	485	460
	8PR	4 J	4 1/2 J		450	560	535
145R13	6PR	3.50B	(4.00B)	4.50B	350	475	460
	8PR	3 1/2 J	4 J	4 1/2 J	450	550	525
155R13	6PR	4.00B	(4.50B)	5.00B	350	510	490
	8PR	4 J	4 1/2 J	5 J	450	595	565
165R13	6PR	4.00B	(4.50B)	5.00B	350	585	560
	8PR	4 J	4 1/2 J	5 J	450	670	640
175R13	6PR	4.50B	(5.00B)	5.50B	350	635	605
	8PR	4 1/2 J	5 J	5 1/2 J	450	730	690
155/80R14	88/86N	4 J	(4 1/2 J)	5 J	350	560	530
165/80R14	91/90N	4 J	(4 1/2 J)	5 J	350	615	600
	97/95N				450	730	690
175/80R14	99/98N	4 1/2 J	(5 J)	5 1/2 J	450	775	750
185/80R14	97/95N	4 1/2 J	(5 J)	5 1/2 J	350	730	690
	102/100N				450	850	800
165R14	6PR	4 J	(4 1/2 J)	5 J	350	615	590
	8PR				450	715	680
175R14	6PR	4 1/2 J	(5 J)	5 1/2 J	350	665	635
	8PR				450	775	735
185R14	6PR	5 J	(5 1/2 J)	6 J	350	725	690
	8PR				450	840	800
195R14	6PR	5 J	(5 1/2 J)	6 J	350	805	770
	8PR				450	935	890
175/80R15	101/99L	4 1/2 J	(5 J)	5 1/2 J	450	825	775
185/80R15	98/96L	4 1/2 J	(5 J)	5 1/2 J	350	750	710
	103/101L	4 1/2 J	(5K)	5 1/2 J	450	875	825
195/80R15	103/101L	5 J	(5 1/2 J)	6 J	350	875	825
	107/105L	5K	5 1/2 K	6K	450	975	925
205/80R15	109/107L	5 J	(5 1/2 J)	6 J	450	1030	975
		5K	5 1/2 K	6K			
215/80R15	112/110L	5 1/2 J	(6 J)	6 1/2 J	450	1120	1060
		5 1/2 K	6K	6 1/2 K			
245/50R13	102L	7JLLT	(7 1/2 JLLT)	8JLLT	450	850	-
235/50R14	102L	7JLLT	(7 1/2 JLLT)		450	850	-
265/50R14	108L	7 1/2 JLLT	8JLLT	(8 1/2 JLLT)	450	1000	-
185/65R15	101/99L	5 J	(5 1/2 J)	6 J	600	825	775
205/65R15	107/105L	5 1/2 J	(6 J)	6 1/2 J	600	975	925
215/65R15	110/108L	6 J	(6 1/2 J)	7 J	600	1060	1000
195/70R15	106/104L	5 J	5 1/2 J	(6 J)	600	950	900
205/70R15	104/102L	5 1/2 K	(6 J)	6 1/2 J	450	900	850
			6K	6 1/2 K			
215/70R15	107/105L	5 1/2 J	6 J	(6 1/2 J)	450	975	925
175/75R15	103/101L	(5 J)	5 1/2 J	5 1/2 K	600	875	825
185/75R15	106/104L	4 1/2 J	(5 J)	5 1/2 J	600	950	900
195/75R15	109/107L	5 J	(5 1/2 J)	6 J	600	1030	975
215/75R15	115/113L	5 1/2 J	(6 J)	6 1/2 J	600	1215	1150
195/85R15	113/111L	5 J	(5 1/2 J)	6 J	600	1150	1090

タイヤサイズ	PR 又はLI等	適用リム ()標準リム				対応空気圧 (kPa)	最大負荷能力(kg)	
							単輪	複輪
195/65R16	106/104L	5 1/2 J	(6 J)	5 1/2 K	(6 K)	600	950	900
205/65R16	109/107L	5 1/2 J	(6 J)	5 1/2 K	(6 1/2 J)	600	1030	975
185/70R16	105/103L	5 J	(5 1/2 J)	6 J	6 K	600	925	875
195/70R16	109/107L	5 J	5 1/2 J	(6 J)	(6 K)	600	1030	975
205/70R16	111/109L	5 1/2 J	(6 J)	5 1/2 K	(6 1/2 J)	600	1090	1030
225/70R16	117/115L	6 J	(6 1/2 J)	(6 1/2 K)	7 J	600	1285	1215
205/75R16	113/111L	5 J	(5 1/2 J)	5 1/2 K	6 J	600	1150	1090
225/75R16	118/116L	(6 J)	(6 1/2 J)	(6 1/2 K)	7 J	600	1320	1250
185/85R16	111/109L	4 1/2 J	(5 J)	4 1/2 K	5 1/2 J	600	1090	1030
195/85R16	114/112L	5 J	(5 1/2 J)	5 1/2 K	6 J	600	1180	1120
205/85R16	117/115L	5 J	(5 1/2 J)	5 1/2 K	6 J	600	1285	1215
215/85R16	120/118L	5 1/2 J	(6 J)	5 1/2 K	(6 1/2 J)	600	1400	1320
225/85R16	121/119L	(6 J)	(6 1/2 J)	(6 1/2 K)	7 J	600	1450	1360
225/50R12.5	98L	[6.75SW]				450	750	-
235/50R13.5	102L	[6.75SW]				450	850	-
245/50R14.5	106L	6.75SW [7.50SW]				450	950	-
215/60R15.5	110/108L	[6.00SW]				600	1060	1000
185/70R15.5	106/104L	[5.25SW] [6.00SW] [5.25SWA]				600	950	900
195/70R15.5	109/107L	5.25SW [6.00SW] 5.25SWA				600	1030	975
195/60R17.5	108/106L	5.25 [6.00]				600	1000	950
205/60R17.5	111/109L	5.25 [6.00] 6.75				600	1090	1030
225/60R17.5	116/114L	6.00 [6.75]				600	1250	1180
195/70R17.5	112/110L	5.25 [6.00]				600	1120	1060
205/70R17.5	115/113L	5.25 [6.00] 6.75				600	1215	1150
	112/110L	(6.00) 6.75				450	1120	1060
215/70R17.5	118/116L	(6.00) 6.75				600	1320	1250
	114/112L	5.25 [6.00]				450	1180	1120
205/80R17.5	120/118L	5.25 [6.00]				600	1400	1320
6.00R15	8PR	[4.50E SDC]			4 1/2 K	450	780	745
6.50R15	10PR	4.50E SDC [5.50F SDC]		4 1/2 K	5K	475	875	835
6.50R15	10PR	[5.50F SDC]				550	970	920
7.00R15	8PR	[5.50F SDC]				450	980	935
7.00R15	10PR	[5.50F SDC]				525	1080	1030
7.00R15	12PR	[5.50F SDC]				600	1180	1120
7.50R15	10PR	5.50F SDC [6.00GS SDC]				575	1280	1215
7.50R15	12PR	[6.00GS SDC]				650	1385	1315
7.50R15	14PR	[6.00GS SDC]				700	1450	1375
6.50R16	8PR	4.50E SDC [5.50F SDC]				475	920	870
	10PR					550	1010	960
	12PR					625	1090	1030
7.00R16	8PR	[5.50F SDC]				450	1025	980
	10PR					525	1130	1075
	12PR					600	1230	1170
7.50R16	10PR	5.50F SDC [6.00GS SDC]				575	1330	1265
7.50R16	12PR	[6.00GS SDC]				650	1440	1370

[]は標準リム、その他は許容リムを示します。
 対応空気圧は最大負荷能力に対する値です。
 100kPa=1kgf/cm²

※空気圧が減少した場合、タイヤの負荷能力に対し荷重超過となり、タイヤが損傷したり事故につながる恐れがありますので設定空気圧を下回らないように注意してください。

月に一度は空気圧の点検を!